

Distinctive by design.

Compact design for flexibility

Hygienic and ergonomic, B4 flourishes in all environments – from boardroom to sports hall. Its compact size, large dispense area for bottles, multiple water options and flexible configuration make it Borg & Overström's most popular model.

Reasons to choose

- Ultra-hygienic touch-sensitive control panel
- High capacity dispense area for bottles and jugs
- Sealed, hygienic, direct-chill cooling system
- Floorstanding option comes complete with an internal alarmed waste kit
- Unique countertop sparkling model



Distinctive by design.

Water system



Direct Chill

Configurations



Countertop





Floorstanding

Water options







Sparkling

Available colours



Black







Distinctive by design.



borgandoverstrom.com

Borg & Overström Totality™



Driven by a relentless pursuit of excellence, Borg & Overström Totality™ is a research and development methodology for the advancement of hygiene, innovation and technology in refreshment systems.



impact resistant epoxy resin panel finish
Providing an increased level of hygiene and longevity,
Fynil™ is a scratch and impact resistant epoxy-resin surface finish - effectively resisting biofilm development and limescale cohesion.

Biofilm, limescale and



World-class filtration
For the ultimate drinking
experience, Borg & Overström
appliances can be pre-fitted
with a 3M filter to reduce
sediment, chlorine, odours
and scale.

Distinctive by design.



Laboratory certified 99.99% bacteria-free Every Borg & Overström appliance undergoes an anti-microbial, antipathogen, sanitising procedure. The reassurance of hygienically safe appliances is provided by the unique bacteria-eliminating process, Sterizen™.



Ultra-violet sterilising system
For added hygiene confidence,
appliances can be fitted with
Viovandt™ – an ultra-violet
sterilisation process that
reduces water-born bacteria.


b4

| Power requirements Hertz 50/Volts 220-240 |
|--|
| Chilled temperature Min 2°C/Max 11°C |
| Hot temperature Max 92°C |
| Throughput litres per hour Chilled & Sparkling 35/Hot 6 |

B4 models

| Countertop W320xD470xH415mm | Water system | Dispense height | Max power consumption | Silver | White | Black |
|---------------------------------------|-----------------|--------------------|-----------------------|--------|--------|--------|
| Chilled & Ambient | Direct Chill | 270mm | 100W | 103510 | 103511 | 103512 |
| Chilled, Hot & Ambient | Direct Chill | 270mm | 600W | 103520 | 103521 | 103522 |
| Chilled, Ambient & Sparkling | Direct Chill | 270mm | 150W | 103530 | 103531 | 103532 |
| Chilled, Hot & Sparkling | Direct Chill | 270mm | 650W | 103540 | 103541 | 103542 |
| Floorstanding W320xD470xH1325mm | | | | Silver | White | Black |
| Internal dimension - W280xD330xH830mm | | | Base cabinet | 103910 | 103591 | 103592 |

Distinctive by design.



Additions for B4



Printed paper cups Environmentally-friendly disposable cups designed to fit Borg & Overström cup

dispensers perfectly.



Deep Sparkle™ CO² refills Can be disposed via standard steel recycling or general waste. Requires CO² regulator with gauge.



Sanitisation kit Six monthly sanitising cycles ensure appliances function at the optimum hygiene levels.



Waste kit overflow sensor Featuring an audible high-water level alarm to prevent the base cabinet waste tank from overflowing. Included as standard on floorstanding models.



Leak detection kit Featuring a moisture sensor that Install appliances simply and shuts the water supply in the unlikely event of a leak.



Install kit with 3M filter effectively in a wide range of applications. Complete with a 3M filter.



Ultra-violet filter kit Complete Viovandt™ filter kit to assist in water purification and removal of unwanted micro-organisms.



Rear cover Tamper-proof rear cover anchors the appliance to the wall and protects plumbing and electrical connections. Ideal for public areas.

Distinctive by design.

Book a visit to the Borg & Overström Academy for a personal demonstration of the new B4

Talk to an adviser +44 (0) 1362 695 006 sales@borgandoverstrom.com

borgandoverstrom.com

Version: B4.05.18.UK (ENG)